

# MATERIAL SAFETY DATA SHEET

PAGE 1 OF 2

<b>IDENTITY</b>	<b>New InkGo®</b> (Original InkGo is now called PermaGo®)
-----------------	--

## SECTION I

<b>MANUFACTURER:</b> A.L. WILSON CHEMICAL CO. 1050 HARRISON AVENUE P.O. BOX 207 KEARNY, NJ 07032	<b>EMERGENCY TELEPHONE NUMBER</b>	800-424-9300 or 703-527-3887
	<b>TELEPHONE NUMBER FOR INFORMATION:</b>	201-997-3300
	<b>DATE PREPARED:</b>	July 1, 2003

## SECTION II - IMPORTANT INGREDIENTS / IDENTITY INFORMATION

IMPORTANT COMPONENTS	CHEMICAL IDENTITY	CAS #	%	TLV
2-(2 BUTOXY ETHOXY) ETHANOL *	C <sub>8</sub> H <sub>18</sub> O <sub>3</sub>	112-34-5	< 5	ND
2-(2 PROPOXYETHOXY) ETHANOL *	C <sub>7</sub> H <sub>16</sub> O <sub>3</sub>	006881-94-3	< 20	ND
ALKYLBENZENES	C <sub>9</sub> -C <sub>11</sub> ALKYLBENZENES	70693-06-0	< 5	ND
PARAFFINS	PARAFFINS C <sub>14</sub> -C <sub>16</sub>	64771-72-8	< 10	300 PPM 8TWA Exxon
2 BUTOXY ETHANOL *	C <sub>6</sub> H <sub>14</sub> O <sub>2</sub>	111-76-2	< 5	20 PPM 8TWA OSHA
OTHER GLYCOL ETHERS *	GLYCOL ETHERS	NA	< 35	ND

\* Subject to SARA, Title III, Section 313 and 40 CFR 372.

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

<b>BOILING POINT</b>	ND	<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1)</b>	approx. .95
<b>VAPOR PRESSURE (mm Hg)</b>	ND	<b>MELTING POINT</b>	NA
<b>VAPOR DENSITY (air =1)</b>	ND	<b>EVAPORATION RATE (butyl acetate =1)</b>	ND
<b>SOLUBILITY IN WATER</b>	Low	<b>FREEZING POINT</b>	ND
<b>APPEARANCE AND ODOR</b>	Clear to light yellow with light sweet odor		

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

<b>FLASH POINT</b> > 185° F Pensky Martens Closed Cup	<b>FLAMMABLE LIMITS</b>	ND
<b>EXTINGUISHING MEDIA</b> water, carbon dioxide "CO <sub>2</sub> ", dry chemical or foam		
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> ND		
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> ND		

## SECTION V - REACTIVITY DATA

<b>STABILITY</b> stable	<b>CONDITIONS TO AVOID</b>
<b>INCOMPATIBILITY (MATERIALS TO AVOID)</b> alkalis, oxidizing agents, reducing agents	
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b> carbon monoxide, carbon dioxide	
<b>HAZARDOUS POLYMERIZATION</b> will not occur	

See Page 2 for more information.

**SECTION VI - HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE**

**EYES:** May irritate.

**SKIN:** May irritate. Prolonged or repeated contact may dry or defat skin.

**INGESTION:** Coughing and vomiting may occur.

**INHALATION:** Overexposure may cause irritation or dryness of nose, throat.

**FIRST AID**

**EYES:** Immediately flush thoroughly with water for 15 minutes.. Get medical attention.

**SKIN:** Immediately flush thoroughly with water. Remove contaminated clothes

**INGESTION:** See a physician as soon as possible.

**INHALATION:** Remove victim to fresh air.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Absorb liquid with paper or use vermiculite, floor absorbent or other absorbent materials. See below.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with federal, state and local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep in cool ventilated place.

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION**

None needed when used with adequate ventilation.

**VENTILATION**

Use in adequately ventilated area.

**PROTECTIVE GLOVES**

rubber or neoprene

**EYE PROTECTION**

Chemical splash goggles recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

**WORK/HYGIENIC PRACTICES**

Wash thoroughly after handling. Do not smoke, eat or drink in work area.

**NA = Not Applicable**  
**ND = Not Determined**

See Page 1 for more information.